

ETL CERTIFIED EVAPORATIVE COOLERS



WORKING IN WARM, COMBUSTIBLE ENVIRONMENTS WHERE WORKER SAFETY IS PARAMOUNT?

Portacool, LLC has ETL Hazardous Location, Class 1, Division 2, Group C and D certification for its Hazardous Location products. Designed to cool areas where airborne gas is potentially combustible, these Hazardous Location products feature sealed switches, cords, motors and pumps to prevent sparking.



ELECTRICAL

All electrical components and connections are sealed in UL listed products to prevent airborne hazards from reaching potential sparks.

SAFETY

Heavy duty pump, motor and switches are optimized for hazardous locations & utilize intrinsically safe brass components.

STANDARDS

Certified ANSI/ISA: 12.12.01.2013 & Conforms to UL St. 507. Cert. to CSA Std. C22.2 No. 104. ANSI/ISA - 12.12.01-2013. Made in USA with domestic and global parts.

| SPECS | 48" | 36" |
|--------------------|------------------------------|-----------------------------|
| Model Number | PAC2K48HZ | PAC2K36HZ |
| Air Delivery | 20,000 CFM / 33,900 m3/hr | 9,600 CFM / 16,300 m3/hr |
| Speeds | One | One |
| Cooling Capacity | 4,000 s.f. / 370 m2 | 2,500 s.f. / 240 m2 |
| Water Reservoir | 40 G / 150 L | 32 G / 120 L |
| Product Dimensions | 86"H x 74"W x 36"D | 67"H x 62"W x 32"D |

PORTACOOOL
PROTECT

| | | |
|--|--|--|
| 1 Year Warranty On All Components | ∞ Lifetime Warranty on all molded housings | 👤 Live US-Based Customer Support |
|--|--|--|



PORTACOOOL
WHEN COMFORT COUNTS™